



Application examples: Three sizes of the Trumpet nozzle pattern are inclusive – two additional nozzle patterns can be retrofitted (top centre and right)

# AIRFLO

Decorative high-performance aerator



- Axial propeller technology for water flow rates up to 295,000 l/h
- Maximum oxygen supply for the body of water
- 3 different, voluminous »Trumpet« type water patterns
- Easy installation and maintenance through bayonet technology
- Foamed float for extraordinary stability
- Pump basket of corrosion-resistant stainless steel
- Fastening set included in the scope of delivery
- Lighting set with stainless steel holder available as an accessory

## Product details



**Bayonet technology**  
for easy mounting.



**Fastening material**  
Easy, secure anchoring of the aerator thanks to the fastening material included in the scope of delivery.



**Earthing pin plug + control box**  
The 230V version is delivered ready-to-operate with control box and earthing pin plug.

**CEE-connector + protection switch**  
The 400V version comes with a ready-to-connect, 5-pole CEE connector and motor protection switch.



1.5 kW Nozzle Superior L		4 kW Nozzle Superior XL		1.5 kW Nozzle Okanagan L		4 kW Nozzle Okanagan XL	
ø m	H m	ø m	H m	ø m	H m	ø m	H m
7	2	10	3.65	6	2	2	3
50349		50350		50333		50348	

## Technical data

		AirFlo 1,5 kW / 230 V	AirFlo 4,0 kW / 230 V
Dimensions (Ø x H)	mm	1150 x 700	1150 x 950
Rated voltage		230 V / 50 Hz	400 V / 50 Hz
Power	kW	1.500	4.000
Power cable length	m	50.00	
Net weight	kg	35.50	49.50
Guarantee	Years	2	
Rated current	A	10.2	9.6
Max. flow rate	l/h	165,000	295,000
Water depth, min.	m	0.90	1.15
Winterproof		No	
Item no.		50183	50185



## Extras

### Top 3 sales arguments

- High-performance aerator and decorative floating fountain in one
- Fast and easy installation and water pattern change
- Variable number of lights (max. 3 x 3) can be retrofitted

### Accessories



#### Illumination Set AirFlo LED

This set supplies an atmospheric, illuminated water feature in the twilight hours and consists of:

- 3 Lunaqua 10 LED spotlights
- 3 stainless steel holders
- 1 underwater transformer incl. special holder
- 50 m cable

Item no. 50479

Lake size		AirFlo 1.5 kW	AirFlo 4 kW
Body of water size at least	m <sup>2</sup>	100	500
Opt. effect for bodies of water up to litres		5000	15000
Suction depth, max.	m	4.00	5.00

Power data of the 3 different AirFlo water patterns (Included in the scope of delivery)		Air Flo 1.5 kW	Air Flo 4 kW
<b>Water pattern M</b>			
Flow rate	l/h	175000	295000
Fountain height x width*	m	0.8 x 3.5	1.5 x 6
<b>Water pattern L</b>			
Flow rate	l/h	160000	265000
Fountain height x width*	m	1 x 5	2 x 8
<b>Water pattern XL</b>			
Flow rate	l/h	125000	225000
Fountain height x width*	m	2 x 6	3.0 x 10

\* Guide values