

Material Safety Data Sheet

Regulation EC No 1907/2006 Art.31

Productname : BELT DRESSING FG **Creationdate :** 15.02.08
Ref.Nr.: UK10580-3-150208 **Replaces:** 30.10.07

1. IDENTIFICATION OF PRODUCT AND COMPANY

Productname : BELT DRESSING FG
Aerosol

Application : Lubricants

Company : **CRC Industries UK Ltd.**
Castlefield Industrial Estate, Wylds Rd, Bridgwater,
Somerset,
UK, TA64DD
Tel.: (+44)(0)1278 727200
Fax: (+44)(0)1278 425644
E-mail : hse.uk@crcind.com

Supplied by:
RS Components Ltd,
 Birchington Road, Corby, Northants, NN17 9RS.
 Tel: +44 (0) 1536 402888 (8am to 8pm)
 Email: technical.help@rs-components.com

In case of emergency : (+44)(0)1278 727200

| Subsidiaries | | Tel | Fax |
|-----------------------------------|--|-------------------------|-------------------------|
| CRC Industries Europe | Touwslagerstraat 1 9240 Zele Belgium | (+32) (0) 52 / 45 60 11 | (+32) (0) 52 / 45 00 34 |
| CRC Industries Finland | Asemanrinne 13, 08500 Lohja AS | (+358)(0)19/32921 | (+358)(0)19/383676 |
| CRC Industries France | 12, Bld des Martyrs de Chateaubriant F-95102 Argenteuil Cédex | (+33)(0)1/34112000 | (+33)(0)1/34110996 |
| CRC Industries Deutschland | Südring 9, 76473 Iffezheim | (+49)(0)7229/3030 | (+49)(0)7229/303266 |
| CRC Industries Iberia | Gremio del cuero S/N, 40195 Segovia | (+34)921/427546 | (+34)921/436270 |
| CRC Industries Sweden | Kryptongatan 14, 43153 Mölndal | (+46)(0)31/7068480 | (+46)(0)31/273991 |

2. HAZARD IDENTIFICATION

Health and Safety : Extremely Flammable
 (propane/butane propellant)
 Irritating to skin.
 Vapours may cause drowsiness and dizziness.
 Remark: Preparations classified as harmful on the basis of an aspiration hazard need not be labelled as harmful with R65 when placed on the market in aerosol containers or in containers fitted with a sealed spray attachment. (EU-Directive 67/548 Annex VI 9.4)

Environment : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



Productname : BELT DRESSING FG **Creationdate :** 15.02.08
Ref.Nr.: UK10580-3-150208 **Replaces:** 30.10.07

Other hazards : Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.
 Without adequate ventilation formation of explosive mixtures may be possible.

3. COMPOSITION AND INFORMATION ON COMPONENTS

| Hazardous ingredient | CAS-nr | EINECS | w/w % | symbol | R-phrases* | Notes |
|---|------------|-----------|-------|--------|-------------------|-------|
| Naphtha (petroleum), hydrotreated light (benzene<0.1%) | 64742-49-0 | 265-151-9 | 30-60 | F,Xn,N | 11-38-51/53-65-67 | B,P |
| Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%) | 68512-91-4 | 270-990-9 | 30-60 | F+ | 12 | K |
| Explanation notes | | | | | | |
| B : substance with national established workplace exposure limit | | | | | | |
| K : not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8) | | | | | | |
| P : not classified as carcinogen, less than 0.1% w/w benzene (Einecs-nr. 200-753-7) | | | | | | |

Note H and P of Annex I (67/548/EEC) apply for the naphtha's in this product.

(* Explanation risk-phrases : see chapter 16)

4. FIRST AID MEASURES

General Advice : The usual precautions for handling chemicals should be observed
 If any symptoms should occur, seek medical advice.

Contact with eyes : If substance has got into eyes, immediately wash out with plenty of water

Contact with skin : Remove contaminated clothing immediately and drench affected skin with plenty of water. Then wash with soap and water
 Seek medical advice

Inhalation : Fresh air, keep warm and at rest.
 Seek medical attention if ill effects occur

Ingestion : Ingestion is unlikely to occur
 If swallowed do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention

5. FIRE-FIGHTING MEASURES

Flash point (without propellant): < 0 °C



| | | | |
|----------------------|------------------|-----------------------|----------|
| Productname : | BELT DRESSING FG | Creationdate : | 15.02.08 |
| Ref.Nr.: | UK10580-3-150208 | Replaces: | 30.10.07 |

Explosion limits : upper limit : not available
lower limit : not available
Extinguishing media : foam, carbon dioxide or dry agent
Fire-fighting procedures : Keep container(s) exposed to fire cool, by spraying with water
Unusual exposure hazard : Aerosols may explode if heated above 50°C

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Shut off all ignition sources
 Ensure adequate ventilation
 Wear suitable protective clothing and gloves.
Environmental precautions : Do not allow to enter public sewers and watercourses
 If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities
Cleaning methods : Absorb spillage in suitable inert material

7. HANDLING AND STORAGE

Handling procedures : Use only in well ventilated areas
 Keep away from heat and sources of ignition
 Do not spray on a naked flame or incandescent material.
 Do not pierce or burn aerosols, even after use.
 Do not breathe aerosols or vapours.
 Avoid contact with skin and eyes.
Storage procedures : Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.
 Keep in a cool, dry, well ventilated place
 Keep out of reach of children.

8. EXPOSURE CONTROL AND PERSONAL PROTECTION

Control procedures : Ensure adequate ventilation
 Keep away from heat and sources of ignition
 Take precautionary measures against static discharges
Personal protection : Use only in well ventilated areas
 It is advisable to take precautions to avoid contact with skin and eyes when handling the product.
inhalation : In case of insufficient ventilation, wear suitable respiratory equipment.
 (Filter type AX)
hands and skin : Wear suitable protective gloves
 (nitrile)
eyes : Wear safety goggles.



| | | | |
|----------------------|------------------|-----------------------|----------|
| Productname : | BELT DRESSING FG | Creationdate : | 15.02.08 |
| Ref.Nr.: | UK10580-3-150208 | Replaces: | 30.10.07 |

9. PHYSICAL AND CHEMICAL PROPERTIES (for aerosols without propellant)

| | |
|--------------------------------------|----------------------------------|
| Appearance : physical state : | propane/butane propelled liquid |
| colour : | colourless |
| odour : | Characteristic odour |
| Boiling point/range : | not available |
| Relative density : | 0.794 g/cm ³ (@ 20°C) |
| pH : | not applicable |
| Vapour pressure : | not available |
| Relative vapour density : | not available |
| Solubility in water : | Insoluble in water |
| Flash point : | < 0 °C |
| Auto-ignition : | > 200 °C |
| Viscosity : | not available |
| Evaporation rate : | not applicable |

10. STABILITY AND REACTIVITY

| | |
|--|--|
| Conditions to be avoided : | Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat and sources of ignition |
| Materials to be avoided : | Strong oxidising agent |
| Hazardous decomposition compounds : | CO,CO ₂ |

11. TOXICOLOGICAL INFORMATION

| | |
|-----------------------|--|
| Inhalation : | Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness |
| Ingestion : | Ingestion is unlikely to occur After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia. |
| Skin contact : | Irritating to skin |

12. ECOLOGICAL INFORMATION

| | |
|--------------------------------|---|
| Other adverse effects : | R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Do not allow to enter public sewers and watercourses |
|--------------------------------|---|

13. WASTE DISPOSAL

| | |
|------------------|---|
| Product : | Do not empty into drains. This material and its container must be disposed of in a safe way. |
|------------------|---|



| | | | |
|----------------------|------------------|-----------------------|----------|
| Productname : | BELT DRESSING FG | Creationdate : | 15.02.08 |
| Ref.Nr.: | UK10580-3-150208 | Replaces: | 30.10.07 |

Disposal should be in accordance with local, state or national legislation

14. TRANSPORT

| | |
|------------------------------|--|
| UN-number : | 1950 |
| Road/Rail - ADR/RID : | UN1950 Aerosols Class : 2, PG : NA, Class code : 5F, Label : 2.1 |
| Sea - IMDG : | UN1950 Aerosols Ltd Qty Class : 2.1, PG : NA, Label : 2.1 |
| EmS | F-D,S-U |
| Air - IATA/ICAO : | UN1950 Aerosols, flammable Class : 2.1, PG : NA, Label : RFG |
| Packing instr. LQ | Y203 |
| PAX | 203 |
| CAO | 203 |

15. REGULATORY INFORMATION

| | |
|----------------------------|---|
| Warning symbol(s) : | F+,Xi,N |
| Risk-phrase(s) : | R12: Extremely flammable. R38: Irritating to skin. R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R67: Vapours may cause drowsiness and dizziness. |
| Safety-phrase(s) : | S2: Keep out of the reach of children. S16: Keep away from sources of ignition - No smoking. S23: Do not breathe spray. S35: This material and its container must be disposed of in a safe way. S51: Use only in well-ventilated areas. |

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Without adequate ventilation formation of explosive mixtures may be possible.

16. OTHER INFORMATION

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.



| | | | |
|----------------------|------------------|-----------------------|----------|
| Productname : | BELT DRESSING FG | Creationdate : | 15.02.08 |
| Ref.Nr.: | UK10580-3-150208 | Replaces: | 30.10.07 |

***Explanation risk-phrases:**

R11: Highly flammable.
R12: Extremely flammable.
R38: Irritating to skin.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65: Harmful: may cause lung damage if swallowed.
R67: Vapours may cause drowsiness and dizziness.

This Material Safety Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Material Safety Data Sheet will be sent to you upon simple request or can be found on our website : www.crcind.com. We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

