



Extras



Top 3 product characteristics

- Energy efficient, warm white 3 W power LED
- Flexible in ground/on ground installation and on wall installation
- An additional spotlight, LunAqua Maxi LED Solo, can be retrofitted in each case

Recommendation

Thanks to the interchangeable optics the half peak angle can be quickly and easily changed from 10° to 30°, to illuminate the garden and pond.

LUNAQUA MAXI LED

Stainless steel design and flexible functionality

- Warm white 3 W power LED in 1 unit or 3 unit set
- Suitable for use underwater and above the water
- Suitable for permanent underwater use, thanks to protection class IP68 (connection IP 44)
- An additional spotlight, LunAqua Maxi LED Solo, can be retrofitted in each case
- Incl. interchangeable optics for a half peak angle of 10° or 30°
- Wall mount and in ground installation possible
- Incl. ground stake and tool for wall mounting
- Star circuit and robust rubber cable

TECHNICAL DATA

		LunAqua Maxi LED Solo	LunAqua Maxi Set 1	LunAqua Maxi Set 3
Dimensions (Ø x H)	mm	52 x 117		
Rated voltage		220–240 V / 50/60 Hz		
Power consumption light fixture	W	3		
Energy efficiency category light fixture*1		A		
Power consumption set	W	–	5	13
Protection class		IP 68	IP 68, IP 44 (transformer)	
Cable length 12 V device	m	2.00 (power unit) + 5.00		
Net weight	kg	1.20	1.80	4.20
Guarantee (+ request guarantee)*P.241	Years	3 + 2		
Illuminant type		LED		
Number of individual LEDs	EA	1		
Light flux	lm	61		
Light colour		Warm-white		
Half peak angle	Degrees	30		
Item no.		50509	50507	50508



*1 Additional instructions concerning the energy efficiency classes are provided on page 235
 *2 Only applies for LunAqua Maxi LED Set 3