



Schematic presentation: Halogen- / LED spotlight systems in use



# LUNAQUA 10 SYSTEM

Powerful and flexible:

The spotlight system for every situation

Lunaqua 10 Halogen



Lunaqua 10 LED /01



- **Optimally matched lighting system**
- **Robust connection technology with many implementation possibilities**
- **Simple mounting via a connecting cable with convenient special connections**

#### Lunaqua 10 Halogen

- Delivered without illuminant, cable and transformer
- Pivot range approximately 180° thanks to the integrated mounting bracket

#### Lunaqua 10 LED /01

- Thermal protection function: Luminous intensity is reduced automatically if the ambient temperature is too high
- Incl. illuminant (not dimmable)
- Additional illuminant available as a spare part, easy replacement
- Pivot range approximately 180° thanks to the integrated mounting bracket
- Illumination range to 12 m

#### Underwater transformer UST 150 /01

- 4 couplings
- Connection of 4 x 35 W, 3 x 50 W, 2 x 75 W halogen or 4 x 10 LED spotlights
- With the PowerBox 12 V up to 12 Lunaqua 10 LED /01 spotlights can be connected (8 spotlights in series on one coupling)



### Lunaqua 10 spotlight

This spotlight offers versatile implementation, whether as lighting for floating fountains or as a flexible light system for every garden.



### Underwater transformer

Simple and safe – this connection technology is unrivalled.



### Connecting cable

This robust rubber cable is available in three lengths.



### Lunaqua 35 Set

Halogen spotlight including 35 W illuminant, transformer and 7.5 m cable.

## Extras

### Top 3 sales arguments

- Optimally matched components
- Spotlight and transformer suitable for underwater implementation
- Flexible even at greater distances

### Recommendation

With the OASE PowerBox 12 V up to 12 Lunaqua 10 LED spotlights can be connected to one UST 150 / 01 (up to 8 units in series).

### Accessories

Halogen illuminant 35 W	Item no. 54035	p. 170
Halogen illuminant 50 W	Item no. 54036	p. 170
Halogen illuminant 75 W	Item no. 54037	p. 170
PowerBox 12 V	Item no. 50492	p. 171

## Technical data

		Lunaqua 10	Lunaqua 10	Underwater transformer	Connecting cable	Connecting cable	Connecting cable	Lunaqua 35
		Halogen	LED /01	UST 150 /01	2,5 m /01	5,0 m /01	7,5 m /01	Set
Dimensions (L x W x H)	mm	145 x 160 x 182		140 x 140 x 89	–			145 x 160 x 182
Rated voltage	V	12		–	–			–
Rated voltage (primary, secondary)		–		230 V / 50 Hz, 12 V	–			230 V / 50 Hz, 12 V
Power consumption	W	35–75	10	150	–			35
Power consumption set	W	–	–	–	–	–	–	40
Light flux	lm	1250*	1250	–	–	–	–	–
Protection class		IP 68						
Power cable length	m	–	–	10.00	2.50	5.00	7.50	8.30
Net weight	kg	0.82	1.12	4.46	0.32	0.56	1.16	2.52
Guarantee	years	2						
Illuminant type		halogen	LED	–	–			halogen
Beam angle	degrees	24°	18°	–	–			24°
Cable cross section	mm <sup>2</sup>	–		–	1.50	1.50	2.50	1.50
Item no.		54034	50366	50401	50402	50403	50404	54314



\* With 50 W illuminant