





WATER TRIO

Luminous fountains for modern garden design



- High quality water feature with three varying fountains, including LED lighting
- »Plug'n Spray« principle: Immediately ready for use and easy connection
- Variations in fountain height (30 140 cm) and light intensity can be played back in permanently set programs
- The programs can be conveniently selected via remote control from a distance of up to 80 m
- Can be connected to a timer
- Flexible setup on a wide variety of substrates
- Robust floor plate protects against damage
- Easy maintenance
- Low energy consumption
- Safe, energy-efficient 12 V technology
- Can be used in swim ponds
- Included in the scope of delivery: 3 pumps / nozzles, external control unit, transformer and cables

PRODUCT DETAILS



External control system

Compact and easy to conceal: The control unit can be easily connected and includes a transformer as well as a ground stake.

The individually controllable nozzles, each

Extras

Top 3 product characteristics

- Remote controlled water feature with varying fountains and white LED illumination
- Easy installation thanks to »Plug'n Spray«
- Can be used in swim ponds



Illuminated nozzles

with 6 LEDs, are easy to align.

Height adjustable The nozzles of the fountain are height adjustable, so that the water level can vary by 20 cm.



Remote control

The remote control unit included in the scope of delivery has a range of up to 80 m without obstruction.

Recommendation

Splash water can be minimised by selecting a pool with at least a 3 m diameter. The OASE water reservoir WR 100 can be extended with pond liner, for example.

TECHNICAL DATA

| | | Water Trio |
|---------------------------------------|-------|--------------------------|
| Dimensions (L x W x H) | mm | 430 x 300 x 240 |
| Net weight | kg | 8.84 |
| Guarantee (+ request guarantee)*P.241 | Years | 2+1 |
| Light colour | | neutral white |
| Cable length 12 V device | m | 2.50 (power unit) + 8.00 |
| Fountain height, max. | m | 1.40 |
| Jet diameter | mm | 5 |
| | | |
| 12 V conrol box | | |
| Dimensions (L x W x H) | mm | 215 x 180 x 305 |
| Power consumption | W | 40 |
| Rated voltage, prim. (control system) | V | 12 |
| Hand-held transmitter/range max. | m | 80.00 |
| | | |
| Power unit | | |
| Dimensions (L x W x H) | mm | 160 x 100 x 100 |
| Rated voltage (primary, secondary) | | 230 V/50 Hz,12 V/DC |
| | | |
| | | |
| Item no. | | 50240 |

P.241 PYEARS PASY INSTALL LOW energy Cost C











Accessories

Water reservoir cover Trio/Quintet Tailored opening for the »Water Trio« and »Water Quintet« fountains. Additional service opening with cover.

Item no. 50327 (page 231)



Water reservoir WR 100 The weather-resistant solution for flexible installation.

Item no. 37112 (page 231)



Pond liner Almost any idea can be a reality with OASE pond liners. Additional information (page 211)

