



Schematic diagram: Underwater filter Filtral UVC (GB-Version) inserted in a pond

FILTRAL UVC



*P. 240

(EXCLUSIVELY AVAILABLE IN GB)

Underwater filter with UVC and fountain



- Suitable for ponds upto 9.000 litres
- A multi talent with filter function and water feature
- Including OASE Clear Water Guarantee^{*P.240}
- Compact filter unit with UVC technology and 4 different filter materials
- Supplied with 90 degree bend and stepped hosetail for feeding a small watercourse or water feature
- Set up completely under water – the appearance of the pond remains undisturbed
- Visual function check of the UVC clarifier
- Can be operated with the additional Filtral Nozzle Kit (50089) to create a fountain effect

PRODUCT DETAILS



Filter media and UVC

Two different filter sponges as well as bio-surface elements and filter pebbles ensure mechanical and biological cleaning. 7/9/11 watt UVC power for clear and healthy water.



Bio-cores and filter pebbles

The filter pebbles in the net bag and the bio surface elements offer adequate settling surface for the micro-organisms.



Integrated UVC unit

7/9 or 11 watt for clear and healthy water.



Coarse particle strainer

Coarse particles of up to 8 mm in size are taken out by the strainer.

TECHNICAL DATA

		Filtral UVC 3000	Filtral UVC 6000	Filtral UVC 9000
Dimensions (L x W x H)	mm	247 x 183 x 160	380 x 290 x 160	
Rated voltage		230 V / 50 Hz		
Power consumption	W	20	38	40
Power cable length	m	10.00		
Net weight	kg	3.18	4.70	
Guarantee*P.241	Years	2		
UVC power	W	7	9	11
Pump capacity max.	l/h	1000	2500	
Max. flow rate	l/h	600	1100	
Meter water column max.	m	1.30	2.30	
Filter intake surface	cm ²	232	564	
Number of blue filter foams	EA	1		
Number of black filter foams	EA	1		
Number of bio-surface elements	EA	2	8	
Special filter granulate	kg	0.20	0.40	
Connection, pressure-side		1"		
Suitable for ponds up to max.	m ³	3.0	6.0	9.0
Suitable for ponds with fish stock	m ³	1.5	3.0	4.5
Exclusively available in GB !				
Item no. (GB-Version only)		51232	51233	51235



Extras

Top 3 product characteristics

- Multifunctional compact solution for prefabricated pools and smaller ponds up to 5 m³
- Clear water, guaranteed
- The technology is virtually invisible because it must be set up underwater

Recommendation

The UVC bulbs should be changed at regular intervals, ideally in spring before the season starts, to guarantee the full strength capacity of the UVC light waves!

Accessories

Tradux

Wall and liner transition for installing either cables or hoses underwater.

Item no. 57154 (Page 219)

Replacement bulb UVC 7 W

Spare bulb for the integrated UVC unit in the Filtral UVC 2500. for BioPress Set 4000.

Item no. 57111 (Page 222)

Replacement bulb UVC 11 W

for BioSmart UVC 16000 for BioPress Set 10000 Spare bulb for the integrated UVC unit in the Filtral UVC 5000.

Item no. 56112 (Page 222)

Replacement filter set Filtral UVC 2500

Consisting of filter sponges, bio-surface elements and filter pebbles.

Item no. 13705 (Page 221)

Replacement filter set Filtral UVC 5000

Item no. 35836 (Page 221)

