

PONDOVAC 4 (EXCLUSIVELY AVAILABLE IN GB)

Convenient pond and pool vacuuming without bothersome interruptions



- Vacuum non-stop thanks to the patented two-chamber system simultaneous vacuuming and emptying of the tank
- Maximum suction depth of 2.4 m thanks to high-performance 1700 W motor with optimised blade geometry
- Can be used for cleaning garden ponds, pools and swim ponds as well as a wet vacuum in the household
- Transparent suction tube for flow-through control
- Easy to move with transport rollers and adjustable handle
- Delivered with special string algae nozzle, widened universal nozzle, wet vacuum brush, brush nozzle for corners and stubborn debris, debris collection bag for retention of coarse particles, 5 m suction hose and 2.5 m discharge hose
- Hand regulator for adjusting the suction power

Product details



Two-chamber system Two same-size cylinders are filled and emptied in alternating cycles. Thus, it is possible to vacuum without bothersome interruptions.



Hand regulator For adjusting the suction power, for example in shallow water.



Wastewater discharge Simply dispose of it as »organic fertiliser« in a flower bed or the sewer.



Handle, transport rollers + suction tube receptacle Fast and convenient transport to the

new implementation site via the adjustable and ergonomic handle.



Debris collection bag Ideal for returning cleaned water when suctioning larger particles > 1 mm. (Not suitable for pond silt)

Extras

Top 3 sales arguments

- Vacuum without interruption thanks to patented two-chamber system
- Maximum suction depth of 2.4 m
- Also ideal for cleaning swim ponds

Recommendation

High-power suction to a depth of 2 m

Included in the scope of delivery

Universal nozzle

The all-round talent (2-10 mm)reliably removes pond floor debris without vacuuming up the gravel.



Special string algae nozzle With this nozzle strands of string algae can be separated and very easily removed.



Brush nozzle For corners and stubborn



Wet suction nozzle Wet suction function for indoors and outdoors.



Technical data

		Pondovac 4
Dimensions (L x W x H)	mm	380 x 415 x 685
Rated voltage		230 V / 50 Hz
Power consumption	W	1700
Power cable length	m	4.00
Net weight	kg	13.06
Guarantee (+ request guarantee)	years	2+1
Water depth, max.	m	2.40
Length, suction hose	m	5.00
Length, discharge hose	m	2.50
		Exclusively available in GB!
Item no. (GB-Version only)		50391

















Accessories

Extension discharge set, **Pondovac**

2.5 m hose with connection union and collection bag for coarse debris particles. Not suitable for pond silt!

Item no. 55448





